

CORBY 29 SPECIFICATIONS

PREAMBLE

The vessel will be built and completed to a high standard consistent with the expectations of her owner and in a manner which brings credit to her designer and builder. She will be fit for purpose in the sense that her detailing and build quality will be considered innovative and in accordance with the best standards of the time whilst ensuring that the vessel is a true offshore yacht suitable to withstand the most rigorous conditions.

HULL & DECK CONSTRUCTION

Female moulded foam cored GRP using isophalic polyester resin, woven glass and closed cell foam. Gabon plywood bulkheads with moulded foam cored GRP furniture.

KEEL

Cast iron fin with lead torpedo bulb. 12 x M20 keel-bolts and stainless steel backing plates inside hull. Fin glass/epoxy sheathed and faired onto hull.

RUDDER

Aluminum Rudder stock with GRP blade Edson roller bearings Custom anodized aluminum "skeleton" tiller with Spinlock tiller extension.

MECHANICAL

Diesel Inboard engine, Yanmar 1GM10 SD Fuel tank 33 lt. (polyurethane) fuel cap & pipe. Engine control panel below deck and single lever throttle. Propeller: Two blade folding.

DECK HARDWARE

Harken/Spinlock deck-gear Winches Harken B40.2STA and B32.2STA, winch handles, jib and mainsail track, general deck gear. Custom stainless steel metal work, guard-wires. Lewmar foredeck and cockpit hatch. Magnetic compass. Life belt with drogue and light

RIG

Aluminium spars with two sets swept back spreaders. Discontinuous Dyeform standing rigging. Spectra/Dyneema ropes. Solid kicker.

ELECTRICAL

Two 12 volt batteries; navigation lights and 6 interior lights. 12v socket and volt meter.

INTERIOR

Forecabin with double berth. Partition to starboard providing privacy to toilet. Main bulkhead with teak trimmed doorway to port leading aft to galley (starboard) and navigation area (port). Galley with stainless steel sink with drain and 2-burner Origo 3000 cooker with gimbals. Hand pumped freshwater from flexible tank with filler. Chart table with chart stowage hinging up to provide access to moulded icebox. Electrical distribution panel and space for electronics above. Four interior lights and one chart lamp. Salon bunks, teak/holly floorboards. Main companionway hatch with sliding perplex cover and removable washboard. Two bilge pumps, one operational below deck as per ORC requirements. Two fire extinguishers.

COSMETIC FINISH

Default colour scheme: white hull and deck with two navy blue waterline stripes. Deck with moulded non-slip effect. White interior with varnished timber edging and floorboards. Upholstery in red or blue marine fabrics.